



### Specifications Rotary unit 2101 mk2

Type	Three-channel Input : Rotary(Acoustic Horn), Stationary-L(Digital Lower Horn), Stationary-R(Digital Lower Horn)
Preamp	Vacuum Tube-preamp and overdrive
Amplifier	Rotary Channel 50W RMS, Stationary Channel 75W RMS x2
Speakers	Horn Driver x1, 15cm-Woofer x2, 5cm-Thweeter x2
Inputs	Leslie 11-pin socket, Leslie 8-pin DIN, Line-in (Mono phone-jack) for Stationary-L, Line-in (Mono phone-jack) for Stationary-R, Line-in (Mono phone-jack) for Rotary, MIDI IN, Foot-sw1(preset), Foot-sw2(slow/fast)
Outputs	Line-out (Stereo phone-jack) for Stationary&Rot.Bass-L/R, Line-out (Stereo phone-jack) for Rotary-L/R, External speaker-connection for Lower L/R, Remote-power, MIDI OUT
Controls	Volume (Sta-L, Sta-R, Rotary), Tube-overdrive with Tube On/Off, Tube-mode, Eight-position function-sw Value Up/Down, Rotor Upper/Lower: Slow-speed, Fast-speed, Rise-time, Fall-time, Break-time, Horn-level, Lower-level, Bass-level, Preset 1-2, Memory, Channel-mode: Sta Mono/Stereo
Dimensions	52cm(W) x 52cm(D) x 32,5cm(H)
Weight	23 kg
Cabinet	High-impact, black leather-like finish
Optional	Stationary Leslie Unit 2121, Stand-adaptor LSA-21, Foot-switch FS-9H, Leslie 11-pin cable, Leslie 8-pin

